Bottle-Top Dispensers DispensMate



- Excellent chemical resistance, components are made of PTFE, FEP, BSG, PP
- Fully autoclavable at 121°C
- Four ranges of bottle-top dispenser covering a volume range from 0.5mL to 50mL
- Easy for cleaning and maintenance
- The optional flexible discharge tube with safety handle permits fast and precise dispensing
- Vapor pressure Max. 500mbar, viscosity max. 500mm²/s, temperature max. 40 °C , density max. 2.2g/cm³
- Dispensemate Plus is supplied with S40, GL32, GL38, GL25, GL28 sized adaptors

Specifications

Cat. No.	Volume Range mL	Graduation mL	A≤±		CV≤	
			%	μL	%	μL
731100017777	0.5-5	0.1	0.5	25	0.1	5
731100027777	1.0-10	0.2	0.5	50	0.1	10
731100037777	2.5-25	0.5	0.5	125	0.1	25
731100047777	5.0-50	1.0	0.5	250	0.1	50

Accessories

Cat. No.	Description		
17000069	S40, Adapter, 45/40mm		
17400017	GL32, Adapter, 45/32mm		
17400018	GL38, Adapter, 45/38mm		
17400019	GL25, Adapter, 32/25mm		
17400020	GL28, Adapter, 32/28mm		
17400037	Reagent Bottle (Brown, 1L, Options)		
17400021	Filling tube(m)		
17100073	Discharge tube(m)		