

Magnetic Stirrers



MS-PA LED Digital Magnetic Stirrer

Features

- Digital speed control with a range of 100-1500rpm
- Max. stirring quantity of H₂O at 3L
- LED display shows speeds
- Nylon+GF housing provides a good performance of weak acids and alkalis resistance

MS-PB Magnetic Stirrer

Features

- A wide range of 0-1500rpm
- Max. stirring quantity of H₂O at 3L
- Nylon+GF housing provides a good performance of weak acids and alkalis resistance



Chemical resistance



Strong magnetism



LED display

Specifications

	MS-PA	MS-PB
Work plate dimensions	φ135(5 inch)mm	φ135(5 inch)mm
Work plate material	Nylon+GF	Nylon+GF
Motor type	DC motor	DC motor
Motor input power	5W	5W
Motor output power	3W	3W
Power	15W	10W
Voltage	100-120/200-240V,50/60Hz	100-120/200-240V,50/60Hz
Stirring positions	1	1
Max. stirring quantity[H ₂ O]	3L	3L
Max. magnetic bar[length]	50mm	50mm
Speed range	100-1500rpm	0-1500rpm
Speed display	LED	Scale
Protection class	IP42	IP42
Dimension [W x D x H]	150×260×80mm	150×260×80 mm
Weight	1.8kg	1.8kg
Permissible ambient temperature and humidity	5-40° C,80%	5-40° C,80%