

Magnetic Hotplate Stirrers

SHCHEER 340° C magnetic hotplate stirrers include all leading safety standards and features for superior easy of use and cost-effective. They are widely used in chemical synthesis, physical and chemical analysis, bio-pharmaceuticals, etc.

MS-H-Pro⁺ LCD Digital Magnetic Hotplate Stirrer

MS-H-Pro^T LCD Digital Magnetic Hotplate Stirrer with Timer

Features

- Brushless DC motor is maintenance free and explosion-proof
- Digital temperature control with Max. temperature at 340° C
- Digital speed control with Max. speed up to 1500rpm
- Max. stirring quantity of H₂O at 20L
- Safety circuits provide overheating protection
- The "HOT" warning will flash when the plate temperature is above 50° C even the hotplate is turned off
- Wide range timer function from 1min to 99h59min(MS-H-Pro^Tonly)
- The high-resolution LCD display shows actual temperatures and speed(MS-H-Pro^Tinclude the time)
- External temperature control is possible by connecting the temperature sensor(PT 1000) with accuracy at ±0.2° C
- Stainless steel work plate with ceramic coating providing good chemical-resistant performance
- Remote function provide PC control and data transmission
- A wide variety of accessories are available



MS-H-S Magnetic Hotplate Stirrer

Features

- Maintenance free brushless DC motor
- Temperature to 340° C
- Stirring speed up to 1500 rpm
- Stainless steel work plate with ceramic coating provides good chemical-resistant performance
- Safety circuits provide overheating protection
- A wide variety of accessories are available



Magnetic Hotplate Stirrers



External sensor



Brushless DC motor



RS232 connector



Chemical resistance



Wide range of accessory



Specifications

	MS-H-PRO ⁺	MS-H-PRO ^T	MS-H-S
Work plate dimensions	φ135mm(5 inch)	φ135mm(5 inch)	φ135mm(5 inch)
Work plate material	stainless steel cover with ceramic	stainless steel cover with ceramic	stainless steel cover with ceramic
Motor type	Brushless DC motor	Brushless DC motor	Brushless DC motor
Motor rating input	18W	18W	18W
Motor rating output	10W	10W	10W
Power	550W	550W	530W
Heating output	500W	500W	500W
Voltage	100-120/200-240V 50/60Hz	100-120/200-240V 50/60Hz	100-120/200-240V 50/60Hz
Stirring positions	1	1	1
Max. stirring quantity[H ₂ O]	20L	20L	20L
Max. magnetic bar[length]	80mm	80mm	80mm
Speed range	100-1500rpm resolution±1rpm	100-1500rpm resolution±1rpm	0-1500rpm resolution±1rpm
Speed display	LCD	LCD	Scale
Temperature display	LCD	LCD	Scale
Heating temperature range	Room temp.-340 ^o C increment 1 ^o C	Room temp.-340 ^o C increment 1 ^o C	Room temp.-340 ^o C
Temperature control accuracy	±1 ^o C(<100 ^o C) ±1%(>100 ^o C)	±1 ^o C(<100 ^o C) ±1%(>100 ^o C)	-
Over temperature protection	360 ^o C	360 ^o C	350 ^o C
Temperature display accuracy	±0.1 ^o C	±0.1 ^o C	±0.5 ^o C
External temperature sensor	PT1000 (accuracy ±0.2)	PT1000 (accuracy ±0.2)	-
"Hot" warning	50 ^o C	50 ^o C	-
Timer function	-	-	1min to 99h 59min
Data connector	RS232	RS232	-
Protection class	IP42	IP42	IP42
Dimension [W x D x H]	160×280×85mm	160×280×85mm	160×280×85mm
Weight	2.8kg	2.8kg	2.8kg
Permissible ambient temperature and humidity	5-40 ^o C 80%	5-40 ^o C 80%	5-40 ^o C 80%