



UNCONTROLLED COPY

NOTES:

1. CARTRIDGE FILTER OPEN AND CLOSED ENDS
2. TWO 1/2" X 5/8" D PROFILE GASKETS
3. 22 GA. & 16 GA. GALVANIZED ENDCAPS
4. EXPANDED METAL 72% MIN. OPEN AREA AT INTERIOR
5. 4 NYLON STRAPS, EVENLY SPACED, ATTACHED WITH ADHESIVE

FILTER MODEL NO.	MEDIA DESCRIPTION	SQ.FT MEDIA AREA	TEMPERATURE RATING
1565954	POLYESTER BLEND	315	180°
1565890	POLYESTER BLEND - FR	315	180°
1565955	POLYESTER BLEND - W/CARBON	350	180°
1565969	POLYGLASS BLEND	350	180°
1565968	POLYGLASS BLEND	341	180°
1566325	POLYESTER BLEND -W/CARBON	325	180°
NF40038	NANOFIBER - FR	315	180°
NF20066	NANOFIBER	315	180°

TOLERANCES (U.O.N.) DECIMAL ± .06 FRACTIONAL ± 1/16 ANGULAR ±+3 - 0	CLARK FILTER		DRAWN BY. JMGj	
	CODE NO.	SCALE NONE	APPROVED BY JMGj	
	TITLE DC CARTRIDGE - GOLD SERIES			
	DATE 12/8/2011	DRAWING NUMBER 23833	REV G	