



UNCONTROLLED COPY

- NOTES:
1. CARTRIDGE FILTER OPEN AND CLOSED ENDS
 2. TWO 1/2" X 5/8" D PROFILE GASKETS
 3. 22 GA. & 16 GA. GALVANIZED ENDCAPS
 4. EXPANDED METAL 72% MIN. OPEN AREA AT INTERIOR
 5. 4 NYLON STRAPS, EVENLY SPACED, ATTACHED WITH ADHESIVE

FILTER MODEL NO.	MEDIA DESCRIPTION	SOFT MEDIA AREA	TEMPERATURE RATING
1565954	POLYESTER BLEND	350	180°
1565890	POLYESTER BLEND - FR	350	180°
1565955	POLYESTER BLEND - W/CARBON	350	180°
1565969	POLYGLASS BLEND	350	180°
1565968	POLYGLASS BLEND	341	180°
1566325	POLYESTER BLEND - W/CARBON	325	180°
NF40038	NANOFIBER - FR	341	180°
NF20066	NANOFIBER	341	180°

TOLERANCES (U.O.N.)		DRAWN BY: JMGj	
DECIMAL	± .06	SCALE	NONE
FRACTIONAL	± 1/16	APPROVED BY	JMGj
ANGULAR	± ± 3 - 0	TITLE: DC CARTRIDGE - GOLD SERIES	

CLARK FILTER	DATE	DRAWING NUMBER	REV
	3/15/2010	23833	F