



# ProTura®

Nanofiber Technology

## TECHNICAL DATA

### FILTER CARTRIDGE SPECIFICATIONS

ITEM NUMBER: NF20010

Dimensions:	Height:	26"
	Outside Diameter:	12.74"
	Inside Diameter:	8.375"
Top End Cap:	Material:	Electro Galvanized (22 ga)
	Style:	Open
Bottom End cap:	Material:	Electro Galvanized (22 ga)
	Style:	Open
Gasket:	1/2" x 1/2" x 10.25" ID isoprene sponge applied on top cap	
Inner Retainer:	Electro galvanized expanded metal 3/8" x 5/8" (9.53 mm x 15.88 mm) 72% open area	
Outer Retainer:	Wire Cage with Hot Melt over Rings	
Filter Media Area:	113 ft <sup>2</sup>	
Pleat Count:	174 +/- 2	
Media Type:	<b>ProTura</b> Nanofiber Technology	
Permeability:	20 cfm/ft <sup>2</sup> @ 0.5" w.g. 160 L/sec/m <sup>2</sup> @ ΔP 20 mm w.g.	
Maximum Temperature:	180° F (82.22° C)	
Minimum Efficiency Reporting Value:	Merv 15 @ 900 cfm	
Particle Efficiency:	99.99% @ 0.5 micron	