DATASHEET

RS-HY7015U7-2 UHF RFID Dry Inlay

KEY DATA

Chip: UCODE 7
Antenna Size: 70 × 15 mm

Format: Dry Inlay, Wet Inlay,


White Paper



APPLICATION

Supply Chain & Clothing Tags Warehouse Management

OVERVIEW



RS-HY7015U7-2 UHF RFID Dry Inlay is built with NXP UCODE 7.

The U7 IC is the leading-edge EPC Gen2 RFID chip that offers best-in-classperformance and features for use in the most demanding RFID tagging applications. Particularly well suited for inventory management application, like e.g Retail and Fashion, with its leading edge RF performance for any given form factor, UCODE 7 enableslong read


distance and fast inventory of dense RFID tag population. With its broadbanddesign, it offers the possibility to manufacture true global RFID label with best-in-classperformance over worldwide regulations.






DATASHEET

DIMENSIONS



ORIENTATION



Physical characteristics	Dimensions
Antenna size	70 × 15 mm
Inlay pitch	25.4 mm
PET width	80 mm
Dry Inlay thickness	Al 10 μm + PET 50 μm
Reel detail	Web width: 80 ± 1.0 mm Inner core diameter: 3" (76.2 mm) Core thickness: 5 ± 2 mm

STRUCTURE

Dry inlay



Chip	
Al 10 µm	
PET 50 µm	





DATASHEET

ELECTRICAL CHARACTERISTICS

	Item	Description
Manufacture/IC		NXP UCODE 7
Base Material		PET
Antenna		Etched AI (10 μm) + PET (50 μm)
Protocol		RAIN RFID / ISO 18000-6C and EPC global Gen2v2 Compliant
Memory	User	None
	TID	48 bits
	EPC	128 bits
	Password	Kill Password - 32 bits
		Access Password - 32 bits
Frequency		860 ~ 960 MHz
Operating Mode		Passive
IC Life		100,000 Programming cycles, 50 years data retention
ESD Voltage Immunity		Max. 2000 V

ENVIRONMENTAL REQUIREMENT

- Operating Temperature/Humidity: -5°C ~ 60°C / 20% ~ 80% RH
- Storage Temperature/Humidity: 20°C ~ 30°C / 20% ~ 60% RH
- Shelf Life: From the date of manufacture, 1 year in anti-static bag at 20° C $\sim 30^{\circ}$ C / $20\% \sim 60\%$ RH, and avoid direct sunlight exposure

PACKAGING

Reference Packing: Static-free bag with zipper; 10000 ± 100 Pcs/roll, 4 rolls/ctn (Actual Qty as per Shipping Mark).

