

| Model | Standard | Category |
|---------------|-------------------|----------|
| L-7296 Yellow | EN ISO 20345:2011 | S1P SRC |

Images



| | |
|---------------------|---|
| Upper: | High Quality Suede Cow Leather |
| Lining: | Abrasion Resistant BK Mesh |
| Insock: | Breathable EVA Insock |
| Outsole: | PU/PU injection, Dual Density |
| Tested : | By UK Intertek Lab (Appoved body:0362) |
| Toe: | Steel Toecap to Resist 200 Joules Impact |
| Penetration: | Steel Plate to Resist 1100 Newtons Puncture |
| Size: | Euro 37-47#, UK 3-13# , US 4-14# |

| SRC | | |
|------------------------------------|-----------------|-------------------|
| SRC (SRA+SRB) | | |
| | PU/PU | PU - PU |
| SRA CERAMIQUE EAU ET | PU/PU ≥ 0.32 | PU - PU ≥ 0.28 |
| SRB PU/PU + GLYCERINE | PU/PU ≥ 0.18 | PU - PU ≥ 0.13 |

EN ISO 20345:2011



Weight & Packages

1. Weight: 1.2-1.3 KGS/Pair
2. Each pair is packed in one color box, box size: 32*23*12CM
3. 10 pairs are packed in one carton, carton size: 62*47*33CM

User Instructions & Storage

1. **RECOMMENDED TO USE:** Basic workplaces, Construction, Logistics, Mechanics, Glasses installation, Workshop, Farming, Garden, Car repair shop etc.
2. **LIMITATION TO USE:** It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
3. **FITTING & SIZE:** All footwear are marked with standard size on tongue label. Some with different size comparison, such as EU size, US size, UK size etc. Please wear footwear by a suitable size. Footwear which are too loose or too tight may not provide optimum level of protection.
4. **STORAGE:** Keep in its original packaging, under ordinary temperature and non-humidity conditions and in clean, covered and ventilated premises.
5. **CLEANING:** Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.

Outsole Material:

The outsole is made of PU/PU material in dual density. The midsole is 45 degree hardness PU, which is soft and shock absorption. The outsole is 60-65 degree hardness PU, which is tough and abrasion resistant. The outsole can pass SRC slip-resistant test.

Insock Material:



J-001 insock design, the ventilation fabric can absorb 90% sweat and dry feet efficiently. U-design support heel can disperse human weight pressure, and reduce friction between feet and shoes. EVA material is soft and flexible, to increase comfortability during walk.

Toecap Protection:



Stainless steel toe cap can reach 200 joules. It is more strong than iron toe cap.

Penetration Protection:



Steel midsole plate, is zero-penetration resistant, which can resist 1100 newtons nail puncture. It is more strong and flexible than normal iron plate.