

Model	Standard	Category
H-9001 White	EN ISO 20345:2011	S2 SRC

Images


Upper:	Waterproof Sunvlar-tech Micro Fiber Leather
Lining:	Abrasion Resistant Sandwich Mesh
Insock:	Breathable EVA Insock
Outsole:	PU/PU injection, Dual Density
Tested :	By UK Intertek Lab (Appoved body:0362)
Toe:	Steel Toecap to Resist 200 Joules Impact
Penetration:	Non Steel Midsole plate
Size:	Euro 37-47#, UK 3-13# , US 4-14#

SRC		
SRC (SRA+SRB)		
SRA CEMENT EAU ET	HLA ≥ 0.32 TACON THICKNESS ≥ 0.28	0.52 0.48
SRB FAIR + GLYCERINE	HLA ≥ 0.18 TACON ≥ 0.13	0.23 0.18

Sole S1
PU - PU
EN ISO 20345:2011


Weight & Packages

1. Weight: 1.3-1.4 KGS/Pair
2. Each pair is packed in one color box, box size: 32*30*12CM
3. 10 pairs are packed in one carton, carton size: 62*62*33CM

User Instructions & Storage

1. **RECOMMENDED TO USE:** Kitchen, Food industry, Cleaning, Cold Storage, Frozen Food Processing, Laboratory Research etc.
2. **LIMITATION TO USE:** It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
3. **FITTING & SIZE:** All footwear are marked with standard size on tongue label. Some with different size comparison, such as EU size, US size, UK size etc. Please wear footwear by a suitable size. Footwear which are too loose or too tight may not provide optimum level of protection.
4. **STORAGE:** Keep in its original packaging, under ordinary temperature and non-humidity conditions and in clean, covered and ventilated premises.
5. **CLEANING:** Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.

Outsole Material:

The outsole is made of PU/PU material in dual density. The midsole is 45 degree hardness PU, which is soft and shock absorption. The outsole is 60-65 degree hardness PU, which is tough and abrasion resistant. The outsole can pass SRC slip-resistant test.

Insock Material:


J-001 insock design, the ventilation fabric can absorb 90% sweat and dry feet efficiently. U-design support heel can disperse human weight pressure, and reduce friction between feet and shoes. EVA material is soft and flexible, to increase comfortability during walk.

Toecap Protection:


Stainless steel toe cap can reach 200 joules. It is more strong than iron toe cap.

Penetration Protection:


Non Steel Midsole plate