

Model	Standard	Category
L-7281	ASTM	M I/75 C/75 PR EH

### Images



<b>Upper:</b>	Full Grain Cow Nubuck Leather
<b>Lining:</b>	Abrasion Resistant Sandwich Mesh
<b>Insock:</b>	Breathable EVA Insock
<b>Outsole:</b>	Goodyear Welted Rubber Outsole
<b>Tested :</b>	By SGS Lab (Notified Body 0598)
<b>Toe:</b>	Steel Toecap to Resist 200 Joules Impact
<b>Penetration:</b>	Steel Plate to Resist 1100 Newtons Puncture
<b>Size:</b>	Euro 37-47#, UK 3-13# , US 4-14#

SRC		
SRC (SRA+SRB)		
SRA CERAMIQUE EAU ET	PU ≥ 0.32 MADE ≥ 0.28	Sole 81 PU - PU 0.52 0.48
SRB PUES + GLYCERINE	PU ≥ 0.18 MADE ≥ 0.13	0.23 0.18

EN ISO 20346:2011



### Weight & Packages

1. Weight: 1.2-1.3 KGS/Pair
2. Each pair is packed in one color box, box size: 32\*21\*12CM
3. 10 pairs are packed in one carton, carton size: 62\*43\*33CM

### User Instructions & Storage

1. RECOMMENDED TO USE: Basic Workplaces, Construction, Logistics, Mechanics, Glasses installation, Workshop, Metal & Related Heat Resistant Industry, Chemical Industry, Oil Industry, Mining etc.
2. LIMITATION TO USE: It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
3. FITTING & SIZE: All footwear are marked with standard size on tongue label. Please wear footwear by a suitable size. Footwear which are too loose or too tight may not provide optimum level of protection.
4. STORAGE: Keep in its original packaging, under ordinary temperature and non-humidity conditions and in clean, covered and ventilated premises.
5. CLEANING: Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.

### Outsole Material:


The outsole is made by natural rubber with 15-20% nitrile, with traditional goodyear welted technology. The thread is sewn by hands with top quality. The rubber sole can pass 300°C hot resistant HRO test, and pass SRC slip-resistant test.

### Insock Material:



J-002 insock design, the ventilation fabric can absorb 90% sweat and dry feet efficiently. U-design support heel can disperse human weight pressure, and reduce friction between feet and shoes. High density EVA is soft and flexible, to increase comfortability during walk.

### Toecap Protection:



Stainless steel toe cap can reach 200 joules. It is more strong than iron toe cap.

### Penetration Protection:



Steel midsole plate, is zero-penetration resistant, which can resist 1100 newtons nail puncture. It is more strong and flexible than normal iron plate.