

Model	Standard	Catagory
H-9430	EN ISO 20345:2011	S3 SRC

**Images**


<b>Upper:</b>	New Design Palm Embossed Cow Leather
<b>Lining:</b>	Abrasion Resistant Sandwich Mesh
<b>Insock:</b>	Breathable EVA Insock
<b>Outsole:</b>	PU/PU injection, Dual Density
<b>Tested :</b>	By UK Intertek Lab (Appoved body:0362)
<b>Toe:</b>	Steel Toecap to Resist 200 Joules Impact
<b>Penetration:</b>	Steel Plate to Resist 1100 Newtons Puncture
<b>Size:</b>	Euro 37-47#, UK 3-13# , US 4-14#

SRC		SRC (SRA+SRB)	
SRA CERAMIQUE	≥ 0.32	0.52	Sole 81 PU - PU
EAU ET	≥ 0.28	0.48	
SRB ASILE + GLYCERINE	≥ 0.18	0.23	DYSC20162011
	≥ 0.13	0.18	


**Weight & Packages**

1. Weight: 1.3-1.4 KGS/Pair
2. Each pair is packed in one color box, box size: 32\*30\*12CM
3. 10 pairs are packed in one carton, carton size: 62\*62\*33CM

**User Instructions & Storage**


1. **RECOMMENDED TO USE:** Basic Workplaces, Construction, Logistics, Mechanics, Glasses installation, Workshop, Farming, Garden, Car repair shop etc.
2. **LIMITATION TO USE:** It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
3. **FITTING & SIZE:** All footwear are marked with standard size on tongue label. Some with different size comparison, such as EU size, US size, UK size etc. Please wear footwear by a suitable size. Footwear which are too loose or too tight may not provide optimum level of protection.
4. **STORAGE:** Keep in its original packaging, under ordinary temperature and non-humidity conditions and in clean, covered and ventilated premises.
5. **CLEANING:** Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.

**Outsole Material:**

The outsole is made of PU/PU material in dual density. The midsole is 45 degree hardness PU, which is soft and shock absorption. The outsole is 60-65 degree hardness PU, which is tough and abrasion resistant. The outsole can pass SRC slip-resistant test.

**Insock Material:**


J-001 insock design, the ventilation fabric can absorb 90% sweat and dry feet efficiently. U-design support heel can disperse human weight pressure, and reduce friction between feet and shoes. EVA material is soft and flexible, to increase comfortability during walk.

**Toecap Protection:**


Stainless steel toe cap can reach 200 joules. It is more strong than iron toe cap.

**Penetration Protection:**


Steel midsole plate, is zero-penetration resistant, which can resist 1100 newtons nail puncture. It is more strong and flexible than normal iron plate.