

Model	Standard	Catagory
L-7501	EN ISO 20345:2011	S1P SRC

Images



- Upper:** Sanvlar-tech Woven Fabric
- Lining:** Breathable Sandwich Air Mesh
- Insock:** Comfortable Mesh Coated EVA
- Outsole:** PU/PU Dual Density
- Tested :** By UK SGS Lab (Appoved body:0120)
- Toe:** Steel Toecap to Resist 200 Joules Impact
- Penetration:** Steel Plate to Resist 1100 Newtons Puncture
- Size:** Euro 37-47#, UK 3-13# , US 4-14#

SRC

SRC (SRA+SRB)

	PLAT	SOLE
SRA CERAMIQUE + EAU ET	≥ 0.32	≥ 0.28
SRB ACIER + GLYCERINE	≥ 0.18	≥ 0.13

Side de PU + PU

EN ISO 20345:2011



Weight & Packages

- Weight: 1.0-1.1 KGS/Pair
- Each pair is packed in one color box, box size: 32*21*12CM
- 10 pairs are packed in one carton, carton size: 62*43*33CM

User Instructions & Storage

- RECOMMENDED TO USE:** Basic workplaces, Construction, Logistics, Mechanics, Glasses installation, Workshop, Farming, Garden, Car repair shop etc.
- LIMITATION TO USE:** It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
- FITTING & SIZE:** All footwear are marked with standard size on tongue label. Some with different size comparison, such as EU size, US size, UK size etc. Please wear footwear by a suitable size. Footwear which are too loose or too tight may not provide optimum level of protection.
- STORAGE:** Keep in its original packaging, under ordinary temperature and non-humidity conditions and in clean, covered and ventilated premises.
- CLEANING:** Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.

Outsole Material:


The outsole is made of PU/PU materal in dual density. The midsole is 45 degree hardness PU, which is soft and shock absorption.The outsole is 60-65 degree hardness PU, which is tough and abrasion resistant. The outsole can pass SRC slip-resistant test.

Insock Material:



J-002 insock design, the ventilation fabric can absorb 90% sweat and dry feet efficiently. U-design support heel can disperse human weight pressure, and reduce friction between feet and shoes. High density EVA is soft and flexible, to increase comfortability during walk.

Toecap Protection:



Stainless steel toe cap can reach 200 joules. It is more strong than iron toe cap.

Penetration Protection:



Steel midsole plate, is zero-penetration resistant, which can resist 1100 newtons nail puncture. It is more strong and flexible than normal iron plate.