

BL-88T

Slit Lamp Microscope



BL-88T · Slit Lamp Microscope

All the optical lenses are moistureproof, mildewproof and anti-reflected treated

Large spot diameter, slit length reach to 14mm, more comprehensive view of the eye condition

Multi-coated optical glass technology, imaging is clear and bright, the view field is wide.

Osram light bulbs, small heat, high-brightness, spot uniformity

Handrail design, user-friendly and the convenience of patients

All the joints can be connected by accessories with international standards

Microscope	Microscope Type	Galilean stereoscopic microscope	
	Magnification Selection	3 steps by drum rotation	
	Eyepiece	12.5x	
	Magnification Ratio (Field of View)	10x(22.5mm), 16x(14mm), 25x(8.8mm)	
	Pupillary Adjustment	50mm ~ 82mm	
	Diopter Adjustment	+7D ~ -7D	
Base	Side Shift	110mm	
	Depth Shift	90mm	
	Height Shift	30mm	
Chin rest	Height Shift	80mm	
	Fixation Target	Red LED	
Illumination system	Slit Width	0 ~ 14mm Continuous(at 14mm, slit becomes a circle)	
	Slit Height	1 ~ 14mm Continuous	
	Slit Angle	0° ~ 180° adjustable	
	Slit Inclination	5°, 10°, 15°, 20°	
	Diameter of Light Spot	φ14mm, φ10mm, φ5mm, φ3mm, φ2mm, φ1mm, φ0.2mm and 1~14mm continuous	
	Filter	Heat Absorption, Grey, Red-Free, Cobalt Blue	
	Illumination Bulb	12v 50w halogen lamp	
	Power	Input Voltage	110V/220V AC
		Frequency	50/60Hz
Power Consumption		68VA	
Weight And Size	Gross Weight	18kg	
	Dimension	690mm (L) × 440mm (W) × 420mm (H)	