

FR/FKR-900

AUTO REFRACTOR

PERFORMANCE FEATURE

- ELECTRIC JAW • ADJUSTABLE DISPLAY LCD
- ROTATING PRISM TECHNOLOGY • AUTOMATIC PAPER CUTTING
- AUTOMATIC TRACKING/FOCUS,AUTOMATIC MEASUREMENT

SPECIFICATIONS

| | |
|---|---|
| Vertex distance | 0、12.0、13.75、15.00mm |
| Spherical degree measurement range | -25.00D ~ +25.00D |
| Column mirror measurement range | -10D ~ +10D |
| Axis measurement range | 0° ~ 180° |
| Interpupillary distance measurement range | 10mm ~ 85mm |
| Minimum measurement pupil diameter | Φ2.0mm |
| Radius of curvature measurement range | 5mm ~ 10mm |
| The measurement range of the principal meridian axis of corneal curvature | 0° ~ 180° |
| Corneal diameter measurement range | 2.0mm ~ 12.0mm |
| Display | 6.5 inch LCD display |
| Printer | Built-in imported thermal printer |
| Power saving mode | 1/5/10/20/40 minutes no operation |
| Power supply | ~220V 50Hz 75VA |
| Size / weight | 255mm (W) X490mm (D) X460-490mm (H) /18kg |

