

		SK-1000A	SK-1000B
Measurement Range	Sphere	-25.00 ~ +25.00D (0.01/0.06/0.12/0.25D)	
	Cylinder Degree	0.00 ~ ±10.00D (0.01/0.06/0.12/0.25D)	
	Cylinder Axis	0°~180° (1°)	
	Addition Degree	0.00 ~ +10.00D (0.01/0.06/0.12/0.25D)	
	Prism Degree	0.00 [△] ~15.00 [△] (0.01/0.06/0.12/0.25D)	
Measurable Lens	single/double optical lens		
	progressive multifocal lens		
	sunglasses (for transmittance measurement)		
Measurement of Prism	polar coordinates ([△] , °) , rectangular coordinates		
Measurement of PD	20.0mm to 48.0mm (monocular PD) , PD of single lens		
Transmittance of UV	support	support	
Transmittance of Bule Light	support	support	
Transmittance of Visible Light	／	support	
Printer	thermal printer		
	manual paper cutting	automatic paper cutting	
	printing paper 58mm×25mm		
Power Supply	main engine: DC 5V		
	power adapter: input AC 110V-240V, 50Hz-60Hz		
Power	30VA		
Size	255mm×210mm×430mm		
Weight	about 5kg		

REDEFINING
FULL
FUNCTIONALITY
EASIER
TO
OPERATE

MULTI FUNCTIONAL
AUTO
LENSMETER



AUTO
LENSMETER
SK-1000A/B



**AUTO LENSMETER
SK-1000A/B**

**Accuracy
Easy
Comfortable**

**“
Pursue for
the Ultimate of
Convenience
and Precision**

Exquisite Design

Only weighs 5kg, soft curved body and classic ivory

Touch Screen

7-inch HD LCD screen for more delicate display

Comfortable touch screen design for smooth operation

Quick

More efficient image-

processing ability

Higher operation speed more

than 15 frames / MS

Fluent

More smooth cursor follow

Linear linkage with monitor

Great measurement accuracy

and speed

· Automatic identification on lens

In automatic measurement mode, the mode can be automatically switched based on specific types of lens

· Measurement of PD and PH

Moving nose slider and with sensor, PD and PH can be automatically generated, which is more convenient and faster

· Measurement of transmittance

the transmittance of blue light, visible light and UV can be measured at the same time, sunglasses with quantitative color intensity can be recommended

