Model: JZJ-9100



Outside Dimension (mm)	7006*5460*3420(L*W*H)	Inside Dimension(mm)	6900*4000*2650(L*W*H)
Front Door(mm)	3000*2600(W*H)	Service Door (mm)	800*2000(W*H)
Total Power	9KW	Total Weight(Ton)	3.8
Cabin System	Wall panel	50mm EPS sandwich panel, steel sheet thickness: 0.426mm	
	Ceiling panel	0.8mm galvanized steel sheet.	
	Front door	Three folds, metal sheet front door	
	Ramps	Two pieces 2000*600mm ramps	
	Basement	300mm depth, two rows grids and three rows checkered plates.	
	Glass	5mm safety tempered glass	
	Windows	Square glass windows	
Air Make-up System	Air inlet fan system	1*7.5kw turbo fan	
	Exhaust fan system	For option	
	Air capacity	22000m ³ /h	
	Exhaust ducting	4 meters straight ducting, one 90°elbow and one 45°elbow.	
Purification System	Pre-filter	G3 grade	
	Ceiling filter	EU5 / F5	
	Floor filter	Green fiber glass filter / G3 grade	
	Exhaust fan filters	Fiber glass filter and active carbon	
Heating System	Heat exchanger	SUS304 material, argon arc welding.	
	Heating burner:	BT14 diesel burner	
	Heating productivity	140000Kcal/h	
	Spray to baking switch	Pneumatic damper	
	Chimney ducting	3 meters stainless ducting and one chimney cap	
	Max heating temperature	80°C	
	Fuel consumption	6-8L/vehicle	
Lighting System	Ceiling lights	8 Units, each 4 * 18W LED lamps. Total 576 W	
	Side lights	For option	
	Illumination	800LUX	
Controlling System	Switched control panel	Spraying & baking switch, lighting switch, emergency stop, breakdown alarm, failure alarm	