

Cable and Litz Wire Division

Key Products:

- ♦ Silk covered wire series
- Wire insulation series
- Wire and cable series

Polyester Yarn Package Paint Copper Wire

Specification Type:

- SDTR Monofilament covered copper wire
- SEDTR Double wire covered copper wire
- SDQZ Monofilament covered copper wire package polyester paint
- SEDQZ Double wire package poly ester paint covered copper wire
- SDQA Monofilament covered copper wire bundle pack polyurethane paint
- SEDQA Double wire package polyurethane paint covered copper wire
- SDQZJ Monofilament package more than polyester thread
- SEDQZJ More than double wire package polyester Strands
- ♦ SDQAJ Monofilament package polyurethane multi-strand line
- SEDQAJ Double wire package polyurethane multi-strand line
- SDQACC Monofilament covered copper wire package special polyurethane paint SEDQACC Double wire bundle of special polyurethane paint covered copper wire

Temperature Class:

A Class (105°C), B Class (130°C), F Class (155°C)

Production Standard:

 Φ 0.07mm ~ 2.0mm

 $\Phi(0.05 \sim 0.50 \text{mm}) \times \text{N Strand} \quad \text{N:3} \sim 950$

Sectional Area:

Less than 4mm₂

Application:

Suitable for manufacturing various electronic instruments, meters, inductance components, and other occasions.





YZPST. YANGZHOU POSITIONING TECH. CO., LTD

Product Standard:

GB11018-89

Note:

- ♦ The technical indicators of polyester yarn covered wire meet the standard requirements
- ♦ Good high frequency electrical performance
- ♦ Polyester silk covered wire with polyurethane enameled wire as the core wire, has good straight soldering performance, solder temperature 375 °C ± 5 °C

P.S. Other types of polyester yarn covered wire can be produced according to customer needs.



