

Silicon Super Fast Recovery Diode

TYPE: YZPST-MUR30040

Features

- High Surge Capability
- Types from 50 V to 400 V V_{RRM}
- Not ESD Sensitive

Symbol	Condition	Ratings	Unit
$I_{F(AV)M}$	$T_C=140^{\circ}C$; 180° sine	300	A
I_{FRMS}	maximum value for continuous operation	425	A
I_{FSM}	$T_j=25^{\circ}C$; t = 8.3 ms (50 Hz); sine	1500	A
I^2t	$T_j=25^{\circ}C$; t = 8.3 ms (50 Hz); sine	-	kA ² S
V_{iso}	A.C.1minute/1second	-	V
T_j		-55 ~ + 150	°C
T_{stg}		-55 ~ + 150	°C
M	mounting torque; ±15%	-	Nm
	terminal torque; ±15%	-	Nm
W	approx.	-	g
I_{RRM}	At V_{RRM} , Single phase, half wave, $T_j=125^{\circ}C$	3	mA
V_{FM}	On-State Current 300A, $T_j=25^{\circ}C$	1.70	V
V_{F0}	$T_j=150^{\circ}C$	-	V
r_F	$T_j=150^{\circ}C$	-	mΩ
t_{rr}	$T_j=25^{\circ}C$; $I_F = 0.5A$; $-di_F/dt = 15A/\mu s$; $V_R = 30V$; $I_{RR} = 0.25A$	90	ns
Q_{rr}	$T_j=150^{\circ}C$; $I_F = 50A$; $-di_F/dt = 100A/\mu s$; $V_R = 100V$	-	us
I_{RM}		-	A
$R_{th(j-c)}$	Per Module	0.45	°C/W
$R_{th(c-h)}$	Per Module	-	°C/W

Outline Drawing

