



CAPACITANCE: 1150 μ f \pm 10%
 MAX CHARGING VOLTAGE: 3KV
 RATED ENERGY@3KV: 5.17KJ
 MAX HOLD TIME AT FULL VOLTAGE: 10S
 NOMINAL REVERSE VOLTAGE: 30%
 MAXIMUM I²t: 3.5*10³ A²s
 MAXIMUM REPETITION RATE: 1 shot/4sec
 MAXIMUM PEAK DISCHARGE CURRENT: 800A
 NOMINAL RMS CURRENT: 30A
 OPERATING TEMPERATURE: -25°C — +60°C
 STORAGE CONDITIONS: -55°C — +80°C
 TANGENT OF LOSS ANGLE: <15*10⁻³ @f=100Hz
 SERIAL RESISTANCE: 0.85 m Ω
 INDUCTANCE: <200nH
 WEIGHT: 36kg

VOLTS DC	KVAR (kvar)	MFD (uf)	FREQ (Hz)	AMPS (A)	Water flow	Water temperature
3000V	0	1150	0	800		

名称	签名	日期
绘制		
检查		
批准		
制造		
验收		

YZPST.
 Yangzhou Positioning Tech. Co., Ltd

I038

MCMJ3.0-1150

A4

重量:

比例1:10

图版 1 (共1)